

## **Instruction for use**

Suits water-based dye-sublimation transfer paper

Jetcol HTR2000

Jetcol HTR3000

Jetcol HTR4000

Jetcol Highspeed

Jetcol TA

### **Instructions for use**

1. This paper has been developed for use as a heat transfer paper for inkjet printing with water-based ink containing disperse sublimation dyestuffs.
2. Unless otherwise stated, the printing side is outside, i.e. the rough side of the paper.
3. Handle the paper with care, roll edges that are deformed or damaged may cause head strikes.
4. Make sure that the paper temperature is the same as the print room temperature.
5. Do not remove the wrapping until you are ready to load the roll into the printer.
6. Do not touch the fresh print, the image will be damaged when the ink is wet or moist.
7. When the printer is not used for extended periods of time, the roll should be re-wrapped in plastic.
8. Follow the instruction of your ink and system supplier in order to achieve the expected transfer result.

### **Important notice**

This paper may not work in all machines and should be tested to determine the suitability of the paper for use in conjunction with your equipment and methods. The Seller and Manufacturer's maximum obligation shall be to replace any paper supplied by them, which has been proven to be defective. Neither the Seller nor the Manufacturer shall be

liable for any injury, direct or consequential, arising from the use of, or the inability to use this paper.

**Remark**

For best results, the printed paper should be sufficiently dry before the transfer.

In the case of Jetcol TA, not all textiles will adhere according to expectations after the transfer. This is (among others) depending on the degree of themostabilisation and the presence of remaining chemicals of the textile production.